

## NRRD Recovery Unit



## Light • Fast

### One Key Operation

- Easy to use

### Twin Cylinder

- Fast recovery

### Oil-Free Compressor

- Suitable for all commonly used refrigerants

### Purge Function

- Prevent mixing of various refrigerants

### High Pressure Protection

- Added safety

| Model                     |         | NRRD  |       |        |        |
|---------------------------|---------|---|-------|--------|--------|
| Refrigerant Type          |         | Category III: R-12, R-134a, R-401C, R-500<br>Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509<br>Category V: R-402A, R-404A, R-407A, R-407B, R-410A, R-507 |       |        |        |
| Power Supply              | V/Hz    | 115V/60Hz   |       |        |        |
| Motor                     | HP      | 1   |       |        |        |
| Max Current Draw          | A       | 10  |       |        |        |
| Compressor                |         | Oil-less, Air-cooled, Piston style  |       |        |        |
| Automatic Safety Shut-Off |         | 558 psi/38.5 bar  |       |        |        |
| Recovery Rate             | lbs/min |   | R-22  | R-134a | R-410a |
|                           |         | Direct Vapor  | 0.49  | 0.31   | 0.44   |
|                           |         | Direct Liquid   | 6.17  | 4.7    | 6.06   |
|                           |         | Push/Pull Liquid  | 11.60 | 10.8   | 12.61  |
| Full Load Amps            | A       | 12  |       |        |        |
| Dimension                 | in      | 18 x 10 x 14  |       |        |        |
| Weight                    | lbs     | 30  |       |        |        |

**1-YEAR WARRANTY**